

LFP CHEMISTRY LITHIUM BATTERY

DATA SHEET

NE2W6130DL

WARRANTY

36

 MONTHS

GENERAL CHARACTERISTICS

Nominal Voltage (V)	60.8
Capacity (Ah) @ 0.2C, 25	30.0
Energy (kWh)	1.82
No. of cell in series	19
No. of cell in parallel	5
Total No. of cell	95
Cell Type	Cylindrical
Chemistry	LFP

ELECTRICAL CHARACTERISTICS

Maximum cut-off voltage (V)	69.35
Minimum cut-off voltage (V)	53.2
Charging Voltage (V)	69.0
Charging Mode	CC-CV
Recommended charging current (A)	10.0
Maximum charging current (A)	15.0
Maximum continuous discharging current (A)	30.0
Peak Discharge Current (A)	40.0 @30Sec
Cell Discharging Protection level (V)	2.8
Cell charging protection level (V)	3.65
Cycle Life @ 0.5C/1.0C @ 25	1500
DOD Level (%)	90%

PROTECTIONS

Cell under voltage protection	Yes
Cell over voltage Protection	Yes
Over Current Protection	Yes
Short circuit protection	Yes
Temperature protection	Yes

TEMPERATURE CHARACTERISTICS

Working Temperature (°C)	0°C - 55°C
Storage Temperature (°C)	0°C - 45°C

OTHERS

Dimension (LXWXH)	(456X196X160) mm
Weight (kg)	18 (Approx)
Power Connector (Charging/Discharging)	SB-120 on side of the battery Pack

WARNINGS

During their use, the batteries should be kept away from heat sources and high voltages.

Do not dismantle or assemble the batteries by yourself.

Do not heat and burn of the batteries and throw them in fire.

Damping of the battery is prohibited.

Avoid charging battery near a fire source or in direct sunlight.

The battery should not be damaged by means of methods like knocking metallic things into the battery, hammering the battery, knocking it violent or etc.

Welding is not allowed to be conducted on the battery.

Do not directly contact with the leaking battery.

NEURON ENERGY

OFFICE : 505, SAI HERITAGE, TILAK ROAD, GHATKOPAR (E), MUMBAI - 400 077

BRANCH : DELHI | MUMBAI | CHENNAI | VARANASI | KOLKATA | **TOLL FREE NUMBER :** 1800-102-2139 | **EMAIL :** SALES@NEURONENERGY.IN